



M2PA Statement of Compliance

Document SQ01505

Version 1.0

©Squire Technologies

This document is the property of Squire Technologies. Information contained herein is confidential. This document, either in whole or in part, must not be reproduced or disclosed to others or used for purposes other than that for which it has been supplied, without Squire Technologies prior written permission, or, if any part hereof is furnished by virtue of a contract with a third party, as expressly authorised under that contract.

Change History

Version	Change Made	Author	Authorised	Date
1.0	Update format, Addition of Change History and Document Number	DR	AC	12.02.14

Contents

1.0	RFC 4165 M2PA Statement of Compliance	4
-----	---	---

1.0 RFC 4165 M2PA Statement of Compliance

Section	Title	Compliance	Notes
1	Introduction	I	
1.1	Scope	I	
1.2	Terminology	I	
1.3	Abbreviations	I	
1.4	Conventions	I	
1.5	Signalling Transport Architecture	C	
1.5.1	Point Code Representation	C	
1.6	Services Provided by M2PA	C	
1.6.1	Support for MTP Level 2/MTP Level 3 Interface Boundary	C	
1.6.2	Support for Peer-to-Peer Communication	C	
1.7	Functions Provided by M2PA	I	
1.7.1	MTP2 Functionality	C	
1.7.2	Mapping of SS7 and IP Entities	C	
1.7.3	SCTP Association Management	C	
1.7.4	Retention of MTP3 in The SS7 Network	C	
1.8	Definition of the M2PA Boundaries	I	
1.8.1	Definition of the M2PA/MTP Level 3 Boundary	C	
1.8.2	Definition of the Lower Layer Boundary Between M2PA and SCTP	C	
1.9	Differences Between M2PA and M2UA	C	Do not support as SG Nodal Interworking Function
2	Protocol Elements	C	
2.1	Common Message Header	C	
2.1.1	Version	C	
2.1.2	Spare	C	
2.1.3	Message Class	C	
2.1.4	Message Type	C	
2.1.5	Message Length	C	
2.2	M2PA Header	C	
2.2.1	Backward Sequence Number (BSN)	C	
2.2.2	Forward Sequence Number (FSN)	C	
2.3	M2PA Messages	C	
2.3.1	User Data	C	
2.3.2	Link Status	C	
	Alignment	C	
	Proving Normal	C	
	Proving Emergency	C	
	Ready	C	
	Processor Outage	C	
	Processor Recovered	C	
	Busy	C	
	Busy Ended	C	
	Out Of Service	C	
2.3.2.1	Link Status Proving	NC	
3	State Control	I	
3.1	SCTP Association State Control	C	
3.2	M2PA Link State Control	C	
4	Procedures	C	
4.1	Procedures to Support MTP2 Features	I	
4.1.1	Signal Unit Format, Delimitation, Acceptance	C	
4.1.2	MTP and SCTP Entities	C	
	IP Address and Port Fully Configurable	C	

4.1.3	Link Alignment	C	
	Proving Period is as MTP2 specifications	C	
	Proving-Interval is configurable	C	
	During T1 Link Status Ready Messages are NOT repeated	C	
4.1.4	Processor Outage	C	
4.1.5	Level 2 Flow Control	C	
4.1.6	Link Out of Service	C	
4.1.7	SCTP Association Problems	C	
4.1.8	Transmission and Reception Priorities	C	
4.1.9	M2PA Version Control	NC	Only compliant to current version 1
4.2	Procedures to Support the MTP3/MTP2 Interface	I	
4.2.1	Sending and Receiving Messages	C	
4.2.2	MTP3 Signalling Link Congestion	C	
4.2.3	Changeover	PC	JT-Q703/JT-Q704 extensions not currently supported
4.2.3.1	Multiple User Data Streams and Changeover	NC	Only single data stream is used
4.3	SCTP Considerations	I	
4.3.1	SCTP Slow Start	C	
5	Examples of M2PA Procedures	I	
5.1	Link Initialization (Alignment)	C	
5.2	Message Transmission and Reception	C	
5.3	Link Status Indication	C	
5.4	Link Status Message (Processor Outage)	C	
5.5	Level 2 Flow Control	C	
5.6	MTP3 Signalling Link Congestion	C	
5.7	Link Deactivation	C	
5.8	Link Changeover	C	
6	Security Considerations	PC	On board firewall capabilities. No onboard support for IPsec or TLS
7	IANA Considerations	C	
7.1	SCTP Payload Protocol Identifier	C	
7.2	M2PA Protocol Extensions	I	
7.2.1	IETF Defined Message Classes	I	
7.2.2	IETF Defined Message Types	C	
7.2.3	IETF-defined Parameter Extension	I	
7.2.4	Defined Values	C	
8	Acknowledgements	I	
9	References	I	
9.1	Normative References	I	
9.2	Informative References	I	

Key :

C	Compliant
PC	Partial Compliance
NC	Non Compliance
I	Information